

# U-RELEASE 1554



**U-RELEASE 1554 is a low viscosity liquid mould release agent based on a blend of waxes with excellent releasing in hard-to-reach zones.**

---

U-RELEASE 1554 is applied by air-less spray with spray gun with reduced air pressure. U-RELEASE 1554 is primarily developed for spray application, it may also be brush or wiped applied, leaving a thin film of waxes thus allowing reproduction of the finest detail.

## **APPLICATION:**

Thoroughly clean the mould with a suitable solvent to remove any previous release or contamination. Wipe dry with a clean cloth.

Using conventional spray equipment (10 – 50 cm from surface), apply U-RELEASE 1554 to the clean moulds. Alternatively, wipe or brush application may be used.

To pre-treat or condition the clean mould, apply three even coats (allow solvent to flash off between coats). For optimum surface results, lightly buff the inside of the mould with a clean, lint-free cotton cloth after drying.

Reapply after each de-mould to ensure the mould is clean and adequate release.

## **CAUTION:**

Use in well ventilated areas. Avoid inhaling vapours or fumes. Avoid contact with skin and eyes. If contact occurs, wash immediately with soap and water. Keep away from heat, sparks and flames and stirring before and during use. Do not store outdoors in case of freezing.

---

## **PRODUCT SPECIFICATIONS**

Colour:	White Liquid
Odour:	Solvent Odour
Specific gravity at 20oC (g/cm <sup>3</sup> ):	0.70
Flashpoint:	-5oC
Flammability Limits:	1-7 % (V)

---