

Material Safety Data Sheet

Page 1 of 6

Issue date: June 2020

U RESIN CC80A PART B

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: U RESIN CC80A Part B

Synonym: None

Use: Polyurethane Elastomer Curative

U RESIN Industrial
4 / 24 Alloa Road,
Maddington, WA, 6109, Australia
www.uresinindustrial.com.au
info@uresin.com.au

Emergency Advice All Hours:

Technical Manager +61 2 9666 3788

2. HAZARDS IDENTIFICATION

HAZARDOUS ACCORDING TO NOHSC CRITERIA

Hazard Category: Harmful (Xn), Irritant (Xi)

Hazard Classification: HAZARDOUS SUBSTANCE, NON-DANGEROUS GOOD

RISK PHRASES

R22 Harmful if swallowed.

R43 May cause sensitisation by skin contact.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SAFETY PHRASES

S24/25 Avoid contact with skin and eyes.

S28 After contact with skin, wash immediately with plenty of water and soap.

S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

S45 In case of accident or if you feel unwell, contact a doctor immediately and show this container or label.

S60 This material and/or its container must be disposed of as hazardous waste.

S61 Avoid release to the environment. Refer to special instructions/safety data sheet.

Poison Schedule: S6 [Aust]

This material is a Scheduled **S6** Poison and must be stored, handled and used according to the appropriate regulations.

Warning Statement:

Do not swallow. Avoid skin contact. Skin contact may cause allergic reaction. Avoid release into the aquatic environment.

3. COMPOSITION / INFORMATION ON INGREDIENTS

SUBSTANCE NAME	Proportion	CAS Number
POLYPROPYLENE GLYCOL	Greater than 60%	25322-69-4
DI-(METHYLTHIO)TOLUENEDIAMINE [DMTDA]	10 to 30%	106264-79-3
MERCURIC PHENYL ESTER (Below Cut-off)	Less than 1%	26545-49-3

All other ingredients not hazardous according to NOHSC Criteria.

Material Safety Data Sheet

Page 2 of 6

Issue date: June 2020

U RESIN CC80A PART B

4. FIRST AID MEASURES

Swallowed:

If swallowed, DO NOT induce vomiting. If person is conscious give water to drink. Seek medical attention immediately.

Eye:

If material is splashed into eyes, immediately, flush with plenty of water for 15 minutes, ensuring eyelids are held open. If irritation persists seek medical attention.

Skin:

If material is splashed onto the skin, remove any contaminated clothing and wash skin thoroughly with water and soap. Flush skin with water. Seek medical attention if irritation persists after washing.

Inhaled:

Remove victim to fresh air. Apply resuscitation if victim is not breathing. If trained personnel available administer oxygen if breathing is difficult.

First Aid Facilities:

Eye wash fountain, safety shower and normal washroom facilities.

Advice to Doctor:

Treat symptomatically.

In case of poisoning, contact Poisons Information Centre

In Australia call Tel: 131126

In New Zealand Tel: 034747000

5. FIRE-FIGHTING MEASURES

Fire/Explosion Hazard

If safe to do so, move undamaged containers from fire area.

HAZARDOUS DECOMPOSITION PRODUCTS: Decomposes on heating emitting oxides of carbon and nitrogen.

FIRE FIGHTING PROCEDURES: Fire fighters to wear Self-contained breathing apparatus (SCBA) in confined spaces, in oxygen deficient atmospheres or if exposed to products of decomposition. Full protective clothing is also recommended.

EXTINGUISHING MEDIA: Use extinguishing media suitable for surrounding fire situation. Use foam, water spray (fog), CO₂ or dry powder. Use water spray to cool fire-exposed containers and for large fires.

HAZCHEM CODE: None allocated [Aust]

FLAMMABILITY

Combustible liquid - Store in accordance with dangerous goods

6. ACCIDENTAL RELEASE MEASURES

Material may be slippery when spilt. Walk cautiously. Ventilate area. Wear protective equipment to prevent skin and eye contact, as outlined under personal protection in this MSDS. Bund area using sand or soil - to prevent run off into drains and waterways. Use absorbent (soil, sand, vermiculite or other inert material). Collect and seal in properly labelled containers for disposal.

7. HANDLING AND STORAGE

Store in a cool place and out of direct sunlight. Store away from sources of heat or ignition. Store away from oxidizing agents. Keep containers closed, when not using the product. Store in original packages as approved by manufacturer. Purge with nitrogen and close container when not in use. Do not eat, drink or smoke in the workplace.

Material Safety Data Sheet

Page 3 of 6

Issue date: June 2020

U RESIN CC80A PART B

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Standards

No exposure standards are available for this product, however, the following exposure standards have been assigned by [NOHSC] to the following components of the product:

POLYPROPYLENE GLYCOL

(ACGIH)

[TWA] 10 mg/m³

DI-(METHYLTHIO)TOLUENEDIAMINE [DMTDA]

No exposure standards have been assigned by the National Occupational Health & Safety Commission (NOHSC)

MERCURIC PHENYL ESTER (Below Cut-off)

(Worksafe Australia)

[TWA] 0.1 mg/m³

Notices: Sk

Engineering Controls

Maintain adequate ventilation at all times. In most circumstances natural ventilation systems are adequate unless the material is heated, reacted or otherwise changed in some type of chemical reaction, then the use of a local exhaust ventilation system is recommended. If exhaust ventilation is not available or inadequate, use approved respirator to Australian Standards.

Personal Protection Equipment

CLOTHING: Wear suitable protective clothing to prevent skin contact.

GLOVES: Wear impervious gloves to prevent skin contact - PVC or natural rubber.

EYES: Wear safety glasses with side shields, chemical goggles or face shield to protect eyes.

RESPIRATORY PROTECTION: Avoid breathing of vapours/gases. Select and use respirators in accordance with AS/NZS 1715/1716. The use of a respirator for organic vapours with (disposable) or with replaceable filters is recommended. Filter capacity and respirator type depends on exposure levels and type of contaminant. If entering spaces where the airborne concentration of a contaminant is unknown then the use of a Self-contained breathing apparatus (SCBA) with positive pressure air supply complying with AS/NZS 1715 / 1716, or any other acceptable International Standard is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Brown-green liquid
Boiling Point Melting Point:	Not determined
Vapour Pressure:	Not determined
Specific Gravity:	1.01-1.04 @ 25°C
Flash Point:	Not determined
Flammability Limits:	Not determined
Solubility in Water:	Negligible

Other Properties

None determined.

10. STABILITY AND REACTIVITY

STABILITY:

Stable under normal conditions of use.

HAZARDOUS DECOMPOSITION PRODUCTS:

Emits toxic fumes including oxides of carbon and nitrogen when heated to decomposition.

HAZARDOUS POLYMERIZATION:

Will not occur under normal conditions of use.

Material Safety Data Sheet

Page 4 of 6

Issue date: June 2020

U RESIN CC80A PART B

INCOMPATIBILITIES:

Strong alkalis, acids, oxidizing agents.

CONDITIONS TO AVOID:

Heat, flames, ignition sources and incompatibles.

11. TOXICOLOGICAL INFORMATION

No adverse health effects are expected, if the product is handled in accordance with this Material Safety Data Sheet and the product label. Symptoms and effects that may arise if the product is mishandled and overexposure occurs are:

ACUTE HEALTH EFFECTS:

Swallowed:

Harmful if swallowed.

May cause irritation to mouth, throat and stomach with effects including mucous build up, irritation to the tongue and lips and pains in the stomach, which may lead to nausea, vomiting and diarrhoea.

Eye:

May cause irritation to the eyes, with effects including: tearing, pain, stinging and blurred vision.

Skin:

Will cause irritation to the skin, with effects including: redness, itchiness, and possible dermatitis.

Inhaled:

May cause irritation to the nose, throat and respiratory system with effects including: dizziness, headache and loss of co-ordination.

Chronic:

Prolonged or repeated skin contact may lead to dermatitis.

Prolonged or repeated exposure may lead to irreversible damage to health.

Prolonged or repeated contact with this substance will cause sensitisation by skin contact.

Toxicological Data:

There is no other toxicological information available for this product.

Toxicological Data for Ingredient(s):

DI-(METHYLTHIO)TOLUENEDIAMINE [DMTDA]:

Acute Oral LD50 (rat) = 1515 mg/kg

Acute Dermal LD50 (rabbit) > 2000 mg/kg

Rats given Di-(methylthio)toluenediamine (DMTDA) in the diet for up to 90 days showed increased liver metabolic activity. There were kidney effects observed that were unique to male rats. These effects were similar to changes that have been observed in male rats given hydrocarbons. These effects resolved in animals allowed 30 days recovery. Rats treated for 24 months did not have microscopic alterations in any tissues compared to the control animals. Tumours seen in control and treated animals were usual for age and strain of rats.

MERCURIC PHENYL ESTER:

LD50 (oral, rat) = 25-200mg/kg

Primary irritant effect on the skin: caustic effect on skin and mucous membranes.

Primary irritant effect on the eye: strong caustic effect.

Sensitisation: no sensitising effect known.

12. ECOLOGICAL INFORMATION

Ecotoxicity:

There is no information available for this product.

Mobility:

There is no information available for this product.

Material Safety Data Sheet

Page 6 of 6

Issue date: June 2020

U RESIN CC80A PART B

AICS - Australian Inventory of Chemical Substances

EPA - Environmental Protection Agency [Int]

NIOSH - National Institute for Occupational Safety and Health [US]

AS/NZS 1715 - Selection, use and maintenance of respiratory protective devices. [Aust/NZ]

AS/NZS 1716 - Respiratory protective devices. [Aust/NZ]

IATA - International Aviation Transport Authority [Int]

ICAO - International Civil Aviation Organization [Int]

IMO - International Maritime Organisation. [Int]

IMDG - International Maritime Dangerous Goods [Int]

United Nations Recommendations for the Transport of Dangerous Goods and Globally Harmonized System for the classification and labelling of Chemicals. [Int]

EU - European Union

[Aust/NZ] = Australian New Zealand

[Int] = International

[US] = United States of America

Removal of the heading of *Poison Schedule [Aust]*, in section 3 and 15 of this Material Safety Data Sheet (MSDS) makes this a valid health and safety document in other international jurisdictions/countries. For full compliance please contact your Federal, State or Local regulators for further information.

Disclaimer

This MSDS summarises our best knowledge of the health and safety hazard information available on the product and the measures to be used to handle and use the product safely. Each user should read this MSDS and consider the information in connection with the way the product is intended to be handled or used.

Principal References:

Information supplied by manufacturer, reference sources including the public domain.

END OF MSDS